



# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet PBFPBX-R-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/09/2016

Revision date: 07/21/2017

Version: 1.1

### DRIVING SURFACE PERFECTION

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Product name : ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)  
Product group : bodyfiller  
Other means of identification : Component of: UP5001 and UP5017

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.3. Details of the supplier of the safety data sheet

###### Supplier

U-POL US Inc  
108 Commerce Way, Stockertown  
PA 18083 - USA  
T 1-800-340-7824 - F 1-800-787-5150  
[technical.department@u-pol.com](mailto:technical.department@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

##### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300 ( UK +44 (0) 1933 230310 (07:30 - 17:00hrs UK time) )

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GHS-US classification

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Repr. 2 H361  
STOT RE 1 H372

Full text of H statements : see section 16

##### 2.2. Label elements

###### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H361 - Suspected of damaging the unborn child  
H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US) :

P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P263 - Avoid contact during pregnancy/while nursing  
P264 - Wash hands thoroughly after handling  
P280 - Wear eye protection, protective clothing, protective gloves  
P302+P352 - If on skin: Wash with plenty of soap and water  
P305 - IF IN EYES: Wash with plenty of water and if necessary take medical advice  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

| Name    | Product identifier | %      | GHS-US classification   |
|---------|--------------------|--------|---|
| styrene | (CAS-No.) 100-42-5 | 5 - 23 | Flam. Liq. 3, H226<br>Acute Tox. 4 (Inhalation), H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Repr. 2, H361<br>STOT RE 1, H372 |

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

|                                       |   |
|---------------------------------------|---|
| First-aid measures general            | : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.   |
| First-aid measures after inhalation   | : Allow victim to breathe fresh air. Allow the victim to rest.  |
| First-aid measures after skin contact | : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Gently wash with plenty of soap and water. Get medical advice/attention. |
| First-aid measures after eye contact  | : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.  |
| First-aid measures after ingestion    | : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.  |

### 4.2. Most important symptoms and effects, both acute and delayed

|                                     |   |
|-------------------------------------|---|
| Symptoms/effects                    | : Suspected of damaging the unborn child. Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation). |
| Symptoms/effects after skin contact | : Causes skin irritation.   |
| Symptoms/effects after eye contact  | : Causes serious eye irritation.  |

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

|                                |  |
|--------------------------------|--|
| Suitable extinguishing media   | : Foam. Dry powder. Carbon dioxide. Water spray. Sand. |
| Unsuitable extinguishing media | : Do not use a heavy water stream.                     |

### 5.2. Special hazards arising from the substance or mixture

|                  |   |
|------------------|---|
| Fire hazard      | : Flammable liquid and vapor.                     |
| Explosion hazard | : May form flammable/explosive vapor-air mixture. |

### 5.3. Advice for firefighters

|                                |   |
|--------------------------------|---|
| Firefighting instructions      | : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. |
| Protection during firefighting | : Do not enter fire area without proper protective equipment, including respiratory protection.   |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

|                  |   |
|------------------|---|
| General measures | : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. |
|------------------|---|

#### 6.1.1. For non-emergency personnel

|                      |  |
|----------------------|--|
| Protective equipment | : Safety glasses. Protective clothing. Gloves. |
| Emergency procedures | : Evacuate unnecessary personnel.              |

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.  
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume, vapors.  
Hygiene measures : Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment.  
Storage conditions : Keep only in the original container in a cool, well-ventilated place away from: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking, ignition sources, heat sources. Keep container tightly closed.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.  
Storage temperature : < 25 °C  
Storage area : Store in a well-ventilated place.  
Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US) |                  |                                 |
|--|------------------|---------------------------------|
| ACGIH                                      | Not applicable   |                                 |
| OSHA                                       | Not applicable   |                                 |
| styrene (100-42-5)                         |                  |                                 |
| ACGIH                                      | ACGIH TWA (ppm)  | 20 ppm                          |
| ACGIH                                      | ACGIH STEL (ppm) | 40 ppm                          |
| ACGIH                                      | Remark (ACGIH)   | CNS impair; URT irr; peripheral |
| OSHA                                       | Remark (OSHA)    | (2) See Table Z-2.              |

### 8.2. Exposure controls

- Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses. Protective clothing.



- Materials for protective clothing : Impermeable clothing.

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                          |  |
|--------------------------|--|
| Hand protection          | : Wear protective gloves.                |
| Eye protection           | : Chemical goggles or safety glasses.    |
| Skin and body protection | : Wear suitable protective clothing.     |
| Respiratory protection   | : Wear appropriate mask.                 |
| Other information        | : Do not eat, drink or smoke during use. |

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

|   |   |
|---|---|
| Physical state                              | : Liquid  |
| Color                                       | : Black   |
| Odor  | : characteristic  |
| Odor threshold                              | : No data available                                     |
| pH  | : No data available                                     |
| Relative evaporation rate (butyl acetate=1) | : No data available                                     |
| Melting point                               | : No data available                                     |
| Freezing point                              | : No data available                                     |
| Boiling point                               | : No data available                                     |
| Flash point                                 | : $\approx 32$ °C                                       |
| Auto-ignition temperature                   | : No data available                                     |
| Decomposition temperature                   | : No data available                                     |
| Flammability (solid, gas)                   | : No data available                                     |
| Vapor pressure                              | : No data available                                     |
| Relative vapor density at 20 °C             | : No data available                                     |
| Relative density                            | : No data available                                     |
| Specific gravity / density                  | : 1.75 - 1.8 g/cm <sup>3</sup>                          |
| Solubility                                  | : insoluble in water. Soluble in aromatic hydrocarbons. |
| Log Pow                                     | : No data available                                     |
| Log Kow                                     | : No data available                                     |
| Viscosity, kinematic                        | : No data available                                     |
| Viscosity, dynamic                          | : No data available                                     |
| Explosive properties                        | : No data available                                     |
| Oxidizing properties                        | : No data available                                     |
| Explosion limits                            | : No data available                                     |

#### 9.2. Other information

|                      |           |
|----------------------|-----------|
| VOC content - Actual | : 250 g/l |
|----------------------|-----------|

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

#### 10.2. Chemical stability

Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

#### 10.3. Possibility of hazardous reactions

Not established.

#### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

#### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity : Not classified

| <b>styrene (100-42-5)</b> |              |
|---------------------------|--------------|
| ATE US (gases)            | 4500 ppmV/4h |
| ATE US (vapors)           | 11 mg/l/4h   |
| ATE US (dust, mist)       | 1.5 mg/l/4h  |

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Based on available data, the classification criteria are not met  
Carcinogenicity : Not classified

| <b>styrene (100-42-5)</b>                |   |
|--|---|
| IARC group                               | 2B - Possibly carcinogenic to humans              |
| National Toxicology Program (NTP) Status | 3 - Reasonably anticipated to be Human Carcinogen |

Reproductive toxicity : Suspected of damaging the unborn child.  
Specific target organ toxicity – single exposure : Not classified  
Specific target organ toxicity – repeated exposure : Causes damage to organs (hearing organs) through prolonged or repeated exposure (Inhalation).  
Aspiration hazard : Not classified  
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.  
Symptoms/effects after skin contact : Causes skin irritation.  
Symptoms/effects after eye contact : Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

| <b>ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)</b> |                  |
|---|------------------|
| Persistence and degradability                     | Not established. |

### 12.3. Bioaccumulative potential

| <b>ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)</b> |                  |
|---|------------------|
| Bioaccumulative potential                         | Not established. |

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer : No additional information available  
Effect on the global warming : No known effects from this product.  
Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Dispose of at authorized waste collection point.  
Additional information : Handle empty containers with care because residual vapors are flammable.  
Ecology - waste materials : Avoid release to the environment.

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1866 Resin solution (flammable), 3, III  
UN-No.(DOT) : UN1866  
Proper Shipping Name (DOT) : Resin solution  
flammable  
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : III - Minor Danger  
DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).  
T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

### Additional information


Emergency Response Guide (ERG) Number : 127  
Other information : No supplementary information available.

### ADR

Transport document description : UN 1866 RESIN SOLUTION, 3, III, (D/E)  
Packing group (ADR) : III  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 30  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Tunnel restriction code (ADR) : D/E  
LQ : 5I  
Excepted quantities (ADR) : E1

### Transport by sea

UN-No. (IMDG) : 1866  
Proper Shipping Name (IMDG) : RESIN SOLUTION  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : III - substances presenting low danger

### Air transport

UN-No. (IATA) : 1866  
Proper Shipping Name (IATA) : Resin solution  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : III - Minor Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

|         |                  |         |
|---------|------------------|---------|
| styrene | CAS-No. 100-42-5 | 5 - 23% |
|---------|------------------|---------|

#### styrene (100-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ : 1000 lb

### 15.2. International regulations

#### CANADA

#### styrene (100-42-5)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2 H319  
Repr. 2 H361  
STOT RE 1 H372

Full text of hazard classes and H-statements : see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

#### styrene (100-42-5)

Listed on IARC (International Agency for Research on Cancer)  
Listed as carcinogen on NTP (National Toxicology Program)  
Listed on EPA Hazardous Air Pollutant (HAPS)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Revision date : 05/08/2017  
Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.  
Other information : None.

# ISOPON PLASTIC BUMPER FILLER (PBFPBX-R-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

|      |  |
|------|--|
| H226 | Flammable liquid and vapor                                     |
| H315 | Causes skin irritation   |
| H319 | Causes serious eye irritation                                  |
| H332 | Harmful if inhaled   |
| H361 | Suspected of damaging fertility or the unborn child            |
| H372 | Causes damage to organs through prolonged or repeated exposure |

### NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

### NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

### NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



### SDS US UPOL

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.*